


# COEX™ C2000 HD IP TriMode Fixed Camera Station with Integrated Junction Box

The COEX™ C2000 HD IP TriMode Fixed Camera Station with integrated junction box has a unique compact and lightweight design developed specifically to meet the worldwide demand for surveillance and process monitoring of harsh industrial and marine environments, providing unprecedented visual feedback in all lighting conditions.



The COEX C2000 marine camera stations are manufactured from the highest-grade, corrosion-resistant, electro-polished 316L stainless steel. They are designed for toughness and durability to operate in the most adverse environments, from freezing temperatures to the blistering heat of desert conditions.

This premium-performance camera station combines Full HD (1080p) video with 30x optical zoom and the latest thermal imaging technology, providing comprehensive coverage of a wide range of specific site applications where the benefits of using visible and thermal imaging are required.

Featuring the latest encoding technology (3<sup>rd</sup> generation IP encoder), the camera station is capable of quad-stream H.264 and H.265 encoding for simultaneous live view and recording.

Utilizing the advanced radiometry feature, the camera station can provide real-time temperature data and differential temperature monitoring of critical devices and applications.

The C2000 HD IP TriMode Fixed Camera Station with integrated junction box has cybersecurity measures built-in, including encrypted video streaming, HTTPS, and 802.1x protocols.

COEX camera stations are compatible with a variety of VMS platforms through ONVIF Profile S and T compliance.

### Options

- Integral wiper
- COEX MEWS5 wash systems
- Advanced radiometry

	<b>316L</b> STAINLESS STEEL	
<b>Direct Ethernet</b>	<b>Quad Streaming</b>	

# Specifications

CERTIFICATIONS / RATINGS <sup>5</sup>		[OPTIONS]
EMC	EN61000-6-2, EN61000-6-4 Class A limits	
CE / UKCA	IEC62368-1	
DNV	Pending	

ENVIRONMENTAL	
Operating Temperature	-45°C to +60°C [+70°C] / -49°F to +140°F [+158°F]
Storage Temperature	-45°C to +80°C / -49°F to +176°F
Ingress Protection	IP66 to IEC60529, Type 6 Enclosure
Salt Mist	IEC60068-2-52 & IEC60945 Section 8.12
Vibration	0.7 g to IEC60068-2-6 & IEC60945
Wind Loading	Operational to 130 km/h, survival to 268 km/h
Humidity	5% to 95%

MECHANICAL	
Material	Electro-polished 316L stainless steel
Window	Optical: HD grade toughened glass, thermostatically operated demister [Wiper <sup>2</sup> ] Thermal: Germanium window with DLC (Diamond-Like Carbon) coating and impact guard
Mounting Orientation	Upright or inverted
Mounting Base	1 x Ø 10.5 mm / 0.41" fixing hole
Dimensions <sup>1</sup> (W x D x H)	402 x 310 x 239 mm / 15.83" x 12.21" x 9.41"
Weight <sup>1</sup>	18 kg / 39.7 lb
Cable Gland Entries	3 x M20 / [3 x M25] / [3 x 1/2" NPT]

ELECTRICAL	Integrated PSU	(Without Integrated PSU)
Input Power Options	(100 to 240) V AC 50/60 Hz	24 V AC/DC (±10%) 50/60 Hz
Power Rating	1.5 A max @ 100 V (Inrush 30 A max)	-
Power Consumption <sup>1</sup>	40 VA Quiescent 50 VA Operating (with heater) 115 VA Max	9 VA Quiescent 14 VA Operating 22 VA Operating (with heater) 27 VA Max
Wash Control <sup>1</sup>	24 V AC/DC (0.75 A max) switched output	
Auxiliary Inputs <sup>3</sup>	1 x contact closure input (5 V pull up) [additional inputs available on request]	
Relay Outputs <sup>3</sup>	1 x volt free switched output (24 V 0.75 A max) [up to 2 available on request]	
Audio <sup>3</sup>	[Line Input]	

CAMERA OPERATION	
Preset Memory	128 user programmable preset positions (zoom, focus)
Wash/Wipe <sup>1</sup>	[Optional wash/wipe with auto-wiper off]
ONVIF Control Features	Zoom and focus control, preset store/recall, auxiliary controls (wash/wipe/auto focus), wash/wipe control mappable to ONVIF presets for control systems that have no support for auxiliary commands, alarm inputs, and relay outputs

**DAY/NIGHT CAMERA / LENS**

Image Sensor	1/2.8" Progressive scan Exmor CMOS sensor
Signal System	1080p 25/30/50/60 FPS
Effective Pixels	Approximately 2.13 megapixels
Zoom Range	30x zoom (up to 360x with digital zoom)
Focal Length / Aperture	4.3 mm (wide) to 129 mm (tele), F1.6 to F4.7
Angle of View (H)	Approx. 64.0° (Wide) to 2.4° (Tele)
Minimum Illumination (50% IRE, High Sensitivity Mode ON)	ICR-OFF mode: 0.009 lx (Shutter Speed: 1/30 s), 0.0012 lx (Shutter Speed: 1/4 s or 1/3 s) ICR-ON mode: 0.00008 lx (Shutter Speed: 1/30 s)
Minimum Illumination (50% IRE, High Sensitivity Mode OFF)	ICR-OFF mode: 0.09 lx (Shutter Speed: 1/30 s), 0.012 lx (Shutter Speed: 1/4 s or 1/3 s) ICR-ON mode: 0.00063 lx (Shutter Speed: 1/30 s)
Minimum Illumination (30% IRE, High Sensitivity Mode ON)	ICR ON mode: 0.000005 lx (Shutter Speed: 1/4 s or 1/3 s, 30%)
Wide Dynamic Range	On/off
Electronic Shutter	Auto (1/1 to 1/10,000 s, 22 steps)
Signal/Noise Ratio	> 50 db (weight on)
Features	Digital zoom on/off, auto/manual focus, auto/manual iris, auto/manual IR cut filter remove (ICR), auto exposure (AE), automatic gain control (AGC), auto white balance (AWB), backlight compensation (BLC), auto slow shutter, wide dynamic range (WDR), defog, on-screen text display (OSD), image invert
Image Stabilization	Super Image Stabilizer (Super/Super+)

<b>THERMAL IMAGER</b>	<b>T306</b>	<b>T318</b>	<b>T618</b>	<b>T636</b>
Image Sensor	Uncooled LWIR VOx microbolometer			
Pixel Pitch	12 μm			
Thermal Sensitivity	<50 mK at f/1.0			
Spectral Response	8- 14 μm			
Refresh Rate	>9Hz [>60Hz] [25 Hz / 30 Hz]			
Pixel Resolution*8	320 x 256		640 x 512	
Fixed Focal Length	6.3 mm f/1.0	18 mm f/1.0	18 mm f/1.0	36 mm f/1.0
Angle of View	34.1° x 27.3°	12.7° x 9.7°	24.3° x 19.5°	12.2° x 9.8°
Radiometric Functionality Available	Yes	No	Yes	No
Features	8x digital zoom, auto/manual gain mode (AGC), auto/manual FFC(NUC), selectable color palettes, second generation digital detail enhancement (DDE), image optimization, active contrast enhancement (ACE), information based histogram equalization (IBHEQ)			
Advanced Radiometry	When used with Synergy, the advanced radiometry feature provides four regions of interest per preset position that can be individually monitored or compared against one another for temperature threshold changes.			

**VIDEO ENCODING**

Compression Standards	H.264 (MPEG4 part 10/AVC) high, main, base profiles H.265 (MPEG-H part 2/HEVC), MJPEG
Bitrate Mode	Constant Bitrate (CBR), Variable Bitrate (VBR)
Encoding Capability	Simultaneous streaming of both day/night and thermal images Up to 2 independently configurable encoded video streams per image sensor
Stream Bitrate*6	100 Kb/s to 25 Mb/s
Image Resolution*6/8	Day/Night Camera: Full HD 1080p (1920 x 1080), 720p (1280 x 720), D1 (720 x 576/480), 4CIF (704 x 576), CIF (352 x 288) Thermal Imager: Native (640x512 or 320x256), D1 (720 x 576/480), VGA (640 x 480), QVGA (320 x 240)
Image Rate*6	Thermal (Full, half, quarter, sixth), HD (up to 60 IPS)
GOP Structure	I-frame only, 5 to 240 frames
Region of Interest (ROI)	Configurable per encoded video stream, ability to crop a selected area of the image source for encoding (variable resolution and aspect ratio)

**AUDIO ENCODING**

Compression Standards	ARM AACLC, ARM AACLC MPEG2, ARM AACHE, ARM AACHE V2
Sample Rate	48 kHz, 44.1 kHz, 32 kHz, 16 kHz
Stream Bitrate	12 to 384 kb/s (AACHE and AACHE V2 32 to 64 kb/s)

NETWORK DEVICE	
Interface Options <sup>*5</sup>	Ethernet (100Base-T, 10-Base-T), Auto/full/half duplex, Auto/10/100, Configurable MTU Size [Fiber optic SFP connectivity] [Media converter]
Protocols	TCP/IP, UDP, ICMP, DHCP, DNS, HTTP, HTTPS, NTP, RTSP/RTP/RTCP, TSRTP, RTMP, RTMPS, SRT, IGMP, SNMP, SYNS, SSL, TLS, 802.1x (EAP)
Control Protocol	SYNS, ONVIF (Profile S, T compliant)
Video Stream Delivery	RTSP/RTP (Unicast: UDP/TCP, Multicast UDP), TSRTP, RTMP, RTMPS, SRT
Network Discovery	SYNS, WS-Discovery (ONVIF)
Device Security	Multiple users and 7 access levels protecting access to the web interface, ONVIF and RTSP services, HTTPS support, HTTP disable, 802.1x (EAP), video streaming disabled until change of default password, unicast stream disable
Supported Internet Browsers	Chrome/Firefox/IE/Edge (No Active-X browser components required)
System Maintenance	Field upgradeable firmware, diagnostic logs Hardware system supervisor providing temperature management, cold-start, auto-shutdown and watchdog control

[FIBER OPTICS] <sup>*5</sup>	100FxLP	100Fx/20km	100Fx/30km	100WLFxA	1000Lx	1000WLxA
Optical Interface	100Base-Fx	100Base-Fx	100Base-Fx	100Base-Fx	1000Base-Lx	1000Base-Lx
Fibers Required	Dual	Dual	Dual	Single	Dual	Single
Wavelength	1310 nm	1310 nm	1310nm	Tx 1310 nm Rx 1550 nm	1310 nm	Tx 1310 nm Rx 1550 nm
Transmit Optical Power	(-20 to -10) dBm	(-15 to -8) dBm	(-5 to 0) dBm	(-14 to -8) dBm	(-9 to -3) dBm	(-9 to -3) dBm
Receive Sensitivity	< -31 dBm	< -31 dBm	< -31 dBm	< -33 dBm	< -22 dBm	< -22 dBm
Standard Optical Link Budget	> 11db	> 16dB	> 26dB	> 19dB	> 13dB	> 13dB
Optical Connector	LC	LC	LC	SC	LC	SC
Fiber Management	Integral fiber management with termination capacity for spare fiber cores					
Features	[Link loss forwarding, fault detection]			Link loss forwarding, fault detection		

[MEDIA CONVERTER] <sup>*5</sup>	Ethernet over Coax
Connectivity	Auto-optimizing for 75 Ω coaxial cable: 280m (920ft) full-rate over video-grade RG-59 (Up to 350m depending on cable quality) 350m (1150ft) full-rate over RG-6 500m (1640ft) full-rate over RG-11
Interface Data Rate	Auto-configuring for speed (10BASE-T or 100BASE-T) and duplex
Features	Retrofit existing analog CCTV installations to Ethernet-based systems, Allow the connectivity of camera stations outside the permitted run length of 100Base-Tx Ethernet cabling

NOTE: \*1 Dependent on certification and equipment fitted. \*2 Wipers are consumable items that need regular replacement. Please refer to the manual for recommendations and maintenance. \*3 Dependent on cable tail option. \*4 Wash output relay option shall be specified at the time of order. \*5 Exact interface option and media type must be specified at the time of order. Maximum transmission distance dependent on cable infrastructure quality and integrity. \*6 Maximum permissible resolution, bitrate and framerate per additional stream will be reduced dependent on the configuration of the primary stream. \*7 Exact certification requirements must be specified at the time of order. \*8 Dependent on lens selection.

## PART CODE STRUCTURE

C2 - A B C D - E - F G H J

(Example) C2 - 2 F 95 T306 - W - B 3 B X

### A - CAMERA HOUSING SIZE

2 Size 2 camera housing

### B - FIXED/PTZ

F Fixed

### C - DAY/NIGHT CAMERA

95 HD (1080p), 30x zoom

### D - THERMAL IMAGING MODULE

T306 Medium resolution, 35° HFOV  
 T318 Medium resolution, 13° HFOV  
 T618 High resolution, 25° HFOV  
 T636 High resolution, 12° HFOV

### E - WIPER

Without wiper  
 W Standard wiper  
 B Brush wiper

### J - SPECIAL

Standard build  
 X Special build

### H - OUTPUT TRANSMISSION TYPE

C Coax  
 E Ethernet Base-T  
 S Singlemode fibre  
 M Multimode fibre

### G - BASE/MOUNTING TYPE

3 Base type 3 (with PSU)  
 4 Base type 4 (without PSU)

### F - TECHNOLOGY SERIES

B 3rd Gen, IP encoder