
COEX™ MEWS Safe-Area Wash System MEWS3

The COEX[™] MEWS3 wash system is developed specifically for Marine and safe-area applications. The wash system allows remote pressure jet washing of the camera station window, maintaining optimum viewing conditions in the harshest of environments.



Designed for operation in marine and safe-area environments, the MEWS3 is the perfect choice to maintain optimum image clarity and performance for COEX C2000 safe-area camera stations.

Comprised of a reservoir and pump, the unit can be installed up to 20 meters below the camera head, allowing servicing and remote operation of the reservoir at ground / deck level. When installed alongside COEX C2000 safe-area camera stations, the water jet is ejected from a spray nozzle mounted on the window wiper arm to ensure uniform window cleaning.

Options

- Wide range of operating voltages
- 10 meter wash hose extension kit
- 5 Liter capacity
- 10 Liter capacity
- 25 Liter capacity




Specifications

CERTIFICATIONS / RATINGS		
EMC	EN61000-6-4, EN61000-6-2	
CE / UKCA	EN/IEC 62368-1	
ENVIRONMENTAL		[OPTIONS]
Operating Temperature	-10°C to +60°C (14°F to 140°F)	
Ingress Protection	IP66 (Wash Pump)	
Wind Loading	Operational to 130 km/h, survival to 200 km/h	
MECHANICAL		
Mounting Bracket	Electro-polished 316L stainless steel	
Painted Bracket	Available on request	
Mounting	5 liters - 4 x Ø 6 mm (Ø 0.24") holes 10 liters - 4 x Ø 6 mm (Ø 0.24") holes 25 liters - 4 x Ø 7 mm (Ø 0.28") countersunk holes	
Reservoir Type	High molecular weight HDPE container	
Reservoir Capacity	5 liters (1 gallon) 10 liters (2 gallons) 25 liters (5.5 gallons)	
Working Pressure	24Vac - 3.8 bar min 115Vac - 1.8bar min 230Vac - 2 bar min	
Pump Seal Material ^{*1}	EPDM	
Fluid Outlet	Ø6mm OD push fit	
Flow Rate	24Vac - > 0.4 liters per minute 115Vac - > 0.9 liters per minute 230Vac - > 0.6 liters per minute	
Dimensions (W x D x H)	5 liters - 260 × 197 × 257 mm (10.24" × 7.76" × 10.12") 10 liters - 344 × 211 × 317 mm (13.54" × 8.31" × 12.48") 25 liters - 397 × 256 × 464 mm (15.63" × 10.08" × 18.27")	
Weight Empty	5 liters - 3.5 kg / 7.7 lbs 10 liters - 4.5 kg / 9.9 lbs 25 liters - 5.5 kg / 12.1 lbs	
Weight Full	5 liters - 8.5 kg / 18.7 lbs 10 liters - 14.5 kg / 32.0 lbs 25 liters - 30.5 kg / 67.2 lbs	

ELECTRICAL		[OPTIONS]
Power Requirements	24Vac - 4.5A 115Vac - 0.9A 230Vac - 0.7A	
Power Consumption	24Vac - 117VA 115Vac - 110VA 230Vac - 120VA	
Electrical Connections	3 x screw terminals for 0.75 - 2.5 mm ²	
Cable Gland Entry	1 × M20	

NOTE: *1 Ensure compatibility with pump seals.



MANUFACTURER OF

Reference Number: 06\DS 0653 lss 1

Synectics sales@synecticsglobal.com

synecticsglobal.com

Specifications subject to change. E & OE. Copyright © Synectic Systems Group Ltd 2021. All Rights Reserved.