12MP IP Fisheye Camera with Edge De-Warping SY-FEE-XYU

The Synectics 12MP Fisheye
Camera matches high resolution
dual stream versatile picture
layout with compact aesthetics.



The Synectics 12MP HD multi-stream IP fisheye camera is equipped with a Sony Exmor™ progressive scan CMOS sensor providing outstanding video resolution.

The camera delivers full 360-degree field of view and simultaneous ability to select a number of optional views including a quad view complete with individual electronic PTZ.

This versatile camera is able to be mounted indoors in both ceiling and wall orientation. With the flexibility this camera can offer it is the ideal choice for many locations to provide wide area surveillance coverage.

* NOTE: Image for representation only, model is supplied with RJ-45 pig-tail.























Specifications


CAMERA	SY-FEE-XYU						
Image Sensor	12MP Sony Exmor 1/1.7" Progressive Scan CMOS						
Effective Pixels	4000 (H) × 3000 (V)						
Resolution	H.264/H.265 (2976 * 2976), (2048 × 2048), (2048 × 1536), (1920 × 1080), (1600 × 1200), (1408 × 1408), (960 × 960), (960 × 720), (960 × 544) MJPEG- Full HD 1080p, (1600 × 1200), (1408 × 1408), (960 × 960), (960 × 720), (960 × 544)						
Min Illumination Color	0.1 Lux						
Min Illumination B&W	0.01 Lux						
Shutter Speed	1 ~ 1/10000 sec						
LENS							
Lens Mount	N/A						
Lens	1.65 mm Fisheye Lens						
FOV	180° @ Full Resolution						
F Number	F2.0						
P Iris	N						
Focus Mode	N/A						
Digital Zoom	8x						
PTZ OPTIONS							
Pan Travel	N/A						
TiltTravel	N/A						
Manual Speed	N/A						
Presets	N/A						
Preset Accuracy	N/A						
Preset Speed	N/A						
Sequence	N/A						
Auto Pan	N/A						
Cruise	N/A						
Proportional Pan / Tilt	N/A						
Home Function	N/A						
Auto Flip	N/A						
Image Rotation	Flip / Mirror / Inverse / Portrait						
STREAMING OPTIONS							
Compression	H.264 / H.265						
ONVIF Profile	G/M/S/T						
Stream	Single Stream: H.264/H.265 2976 × 2976 @ 27 fps, 2048 × 2048 @ 30 fps Dual Stream: H.264/H.265 2048 × 2048 @ 25/30fps 1920 × 1080 @ 25/30fps						
Stream 1 Max Resolution and FPS	H.264/H.265 2976 x 2976 @ 27 fps						
Stream 2 Max When Stream 1 Set Max Resolution and FPS	H.264/H.265 960x960 @ 15fps						
Min/Max Bitrate	64/20480 (kbps)						

OPERATION							
OPERATION	A - 10 10" 10						
ICR	Auto / On / Off / Smart						
LED Numbers	4						
LED Distance	Up to 5 m						
White Balance	Manual / AWB / ATW / One Push						
NR	2D / 3D / Color						
BLC	On / Off						
WDR	Gamma WDR						
DIS / EIS	N						
Motion Detection	On / Off / Schedule						
Privacy Mask Type	8 Colors / 5 Sets						
Tamper Alarm	On / Off / Schedule						
AudioType	Built-in Speaker (Max. 2W Mono) & Microphone						
Audio In	AAC / G.711 / G.726						
Audio Out	AAC / G.711 / G.726						
Audio Sample Rate	ACC: 48000 / Other: 8000						
Analog Out	N/A						
Heater	N/A						
Fan	N/A						
Alarm Input	1 Set						
, Indiana in the second of the	5V 10kΩ Pull Up						
Alarm Output	1 Set Photo Relay Output 300V DC / AC						
Event Notification	HTTP / FTP / SMTP						
SD Card Support							
Ethernet Connector	microSDXC 128GB						
Power Connector	RJ-45 pig-tail cable						
	PoE only						
I/O Connector	8 Pin Terminal Block, Pitch 2.5 mm						
Protocol	IPv4/v6, TCP/IP, UDP, RTP, RTSP, HTTP, HTTPS, ICMP, FTP, SMTP, DHCP, PPPoE, UPnP, IGMP, SNMP, QoS, ONVIF G, ONVIF M, ONVIF S, ONVIFT						
Security	HTTPS / IP Filter / IEEE 802.1X						

ENVIRONMENTAL

Operating Temperature -10°C ~ 50°C (14° ~ 122° F) Storage Temperature -20°C ~ 65°C (-4° ~ 149° F) Humidity 10% ~ 90%, No Condensation IK10 Vandal Resistant

GENERAL	
Power	PoE
Power Priority	N/A
Power Failover	N/A
PoE Classification	Class 0
Power Consumption (Total Unit)	Maximum of PoE: 9.5W
Dimensions	Ø 130 x 61.5 mm / Ø 5.1 x 2.4"
Weight	330 g / 0.73 lb
Certification	CE / FCC



^{*1} Standalone accessory, no further accessories are required.




The following are required in combination with other accessories for mounting requirements.

PRODUCT	SY-FEE-A-22	SY-CM-P	SY-CM-MP	SY-CM-T25	SY-CM-T50	SY-CM-T100	SY-CM-15NTP	SY-CM-WMB	SY-CM-CWM	SY-CM-PMB
Wall Mounting	Required	~	~					~	✓	✓
Pole Mounting	Required			✓	~	~				
Non-Synectics Bracketry	Required						Required			

Fish Eye Accessories Addendum and Diagrams

IN CEILING MOUNT — SY-FEE-ICM-22



Cut Hole size: 147 mm

WALL MOUNT BRACKET — SY-FEE-WM-22

