

COEX™ C2000 TriMode Series '6' Fixed Camera Station

The COEX™ C2000 TriMode Fixed camera station 6 series has been specifically developed for marine applications and demanding environments. Combining the latest thermal imaging technology with a day / night (colour / mono) camera module the C2000 TriMode camera stations ensure unprecedented visual feedback in all light conditions.



Utilised around the world to assist with:

- Pipeline monitoring
- Navigation during night time and foggy conditions
- Ice Detection
- Piracy Detection
- Man-overboard Safety
- Environmental Protection
- Intruder Detection
- Safety and Security Protection

Even during daylight the C2000 TriMode can provide increased visibility over conventional camera stations with human detection at over 1100 m^{*3/4}

COEX Series 6 camera stations are fitted with a 640 x 512 thermal imaging camera and a high resolution analogue day / night camera with removable IR cut filter.

Features

- CSAus Certification
- CSA Canadian Certification
- EAC-TR CU Certification
- IP66 & IP67 rated – completely protected against dust & water ingress, for the most extreme environments
- Electro-polished 316L stainless steel, for maximum corrosion resistance
- TriMode Operation – Day (colour), Night (mono) and Thermal Imaging
- Low Voltage Operation
- Germanium and Toughened Glass Windows

Options

- Integral Wiper [W]
- COEX™ "MEWS" Pressurised Wash System
- Synectics IP and Fibre Optic Transmission (via associated junction box)
- COEX™ Wall Mount Bracket
- COEX™ Range of Tilt Down Towers and accessories

Specifications

CERTIFICATIONS / RATINGS		[OPTIONS]
Certifications / Ratings	CSAus / CSA Canadian Class 3862 13 and Class 3862 93 EAC-TR CU Certified IP66 & IP67 to IEC 60529 CE Compliant to EMC and Low Voltage Directives LVD Directive: 2006/95/EC	
ENVIRONMENTAL		
Operating Temperature	-45°C to +70°C	
MECHANICAL		
Material	Electro-polished 316L Stainless Steel	
Windows	Germanium and Toughened Glass, Thermostatically Operated Demister [Wiper for Day / Night View only]	
Mounting	1 x M10 Hole	
Dimensions (W x D x H)	2172 x 310 x 250.2 mm	
Weight	9 kg	
ELECTRICAL		
Power Requirements	24Vac 50 / 60Hz or 24Vdc (±10%)	
Power Consumption	92VA Maximum	
TELEMETRY		
Interface	RS485 serial asynchronous data	
Protocols*2	Synectics™, Pelco®, and other industry standard protocols available	
Functions*1	Wash, Wipe, Aux1, [Aux2] and Aux in	
Day/Night Camera Functions*1	On / Off Selection of: Digital Zoom, BLC, Autofocus; Auto / Manual Selection of: Focus, Colour / Mono Operation, Frame Integration, White Balance	
Thermal Camera Functions*1	3 step digital zoom (2x, 4x, 8x), Multiple Colour Palettes (including Inverted), Cross Hair Temperature Display, Auto / Manual Shuttering	
OSD	Password protected on-screen menu system for camera station configuration and diagnostics	
CAMERA / LENS		
	C2000-2F36-T6>> [W]*5	C2000-2F10-T6>> [W]*5
Video Output	1.0 Vpk-pk CVBS into 75Ω; Colour PAL 50Hz [NTSC 60Hz]	
Image Sensor	¼" EXview HAD CCD	⅓" Super HAD CCD II
Resolution	>550TVL	>530TVL
S/N Ratio	>50dB	
Zoom Range	36x zoom (up to 432x with digital zoom)	10x zoom (up to 120x with digital zoom)
Minimum Illumination	1.4 lux 0.1 lux (with ⅓ sec integration) 0.01 lux mono (with ⅓ sec integration)	0.25 lux 0.015 lux (with ⅓ sec integration) 0.0004 lux mono (with ⅓ sec integration)
Focal Length	3.4 to 122.4 mm	5.1 to 51 mm
Angle of View	57.8° to 1.7°	52° to 5.4°
Aperture	F1.6 to 4.5	F1.8 to 2.1
THERMAL IMAGER		
	C2000-2F<<-T650 [W]*5	C2000-2F<<-T625 [W]*5
Image Sensor	Uncooled VOx Microbolometer	
Spectral Response	8 – 14 μm	
Thermal Sensitivity	>50mK	
Refresh Rate	<9Hz [25Hz]	
Resolution	640 x 512	
Fixed Focal Length	50 mm	25 mm
Angle of View	12.4° x 9.9°	25° x 20°
Human Detection*3/4	~1100 m	~560 m

NOTE: *1 Dependant on equipment fitted. *2 Refer to Synectics for availability and compatibility with other control systems *3 Based on Johnson Criteria. *4 Actual range may vary depending on camera set-up, user experience, environmental conditions and type of monitor or display used. *5 >> replace with thermal camera module and << replace with day / night camera module.

Synectics

sales@synecticsglobal.com

synecticsglobal.com

Specifications subject to change. E & OE.

Copyright © Synectic Systems Group Limited, Synectic Systems, Inc., Synectic Systems (Asia) Pte. Limited 2018. All Rights Reserved.

MANUFACTURER OF



CAMERA STATIONS

Reference Numbers: 03GF620_2
C2000T2FS6/0418/A4 Iss 4