

# COEX™ C3000 TriMode Series '6' Ex d Camera Station

The COEX™ C3000 TriMode camera station 6 series has a unique compact and lightweight design specifically developed for hazardous area applications. Combined with the latest thermal imaging technology with a day / night (colour / mono) camera module the C3000 TriMode camera stations ensure unprecedented visual feedback in all light conditions.



Utilised around the world to assist with:

- Pipeline monitoring
- Navigation during night time and foggy conditions
- Ice Detection
- Piracy Detection
- Man-overboard Safety
- Environmental Protection
- Intruder Detection
- Safety and Security Protection

Even during daylight the C3000 TriMode can provide increased visibility over conventional camera stations with human detection at over 1100 m<sup>3/4</sup>

COEX Series 6 camera stations are fitted with a 640 x 512 thermal imaging camera and a high resolution analogue day / night camera with removable IR cut filter.

## Features

- ATEX II 2 GD Certification
- IECEx Certification
- Ex d IIC, T4, T5 or T6
- EAC-TR CU Certification
- DNV Type Approval
- IP66 & 68 Rated – completely protected against dust & water ingress, for the most extreme environments
- Electro-polished 316 stainless steel, for optimum corrosion resistance
- TriMode Operation – Day (colour), Night (mono) and Thermal Imaging
- Low Voltage Operation
- Preset accuracy and repeatability of <math><0.05^\circ</math>
- Pre-Heat Mode for safe start up in freezing conditions

- Smart Move Technology assists target acquisition and tracking
- Germanium and Toughened Glass Windows

## Options

- Continuous Rotation [C]
- Absolute Positioning
- Integral Wiper [W]
- COEX™ "FEWS" Ex Pressurised Wash System
- Integral Fibre Optic Transmission (via alternative base)
- Fibre Optic Transmission (via associated junction box)
- IP within the Camera Housing
- COEX™ Wall Mount Bracket
- COEX™ Range of Tilt Down Towers and accessories

# Specifications

CERTIFICATIONS / RATINGS		[OPTIONS]
Certifications / Ratings	Ex d IIC T4 / T5 / T6 Gb; Ex tb IIIC T4 / T5 / T6 Db; ATEX II 2GD IECEX EAC-TR CU DNV Type Approval CE Compliant to EMC Directive IP66 & IP68 to IEC 60529 (30m Submersion for 4 hrs)	
ENVIRONMENTAL		
Rated Temperature	-45°C to +60°C [+70°C]	
MECHANICAL		
Material	Electro-polished 316 Stainless Steel	
Windows	Germanium and Toughened Glass, Thermostatically Operated Demister [Wiper for Day / Night View only]	
Pan Operation	362° rotation @ 0° to 42°/sec; Mechanical Limits; Programmable Soft-stops; Preset Positioning [Continuous Rotation]	
Tilt Operation	180° rotation @ 0° to 21°/sec; Mechanical Limits; Programmable Soft-stops; Preset Positioning	
Mounting	4 x M8 tapped holes, equispaced on a 4" (101.6 mm) P.C.D.	
Dimensions (W x D x H)	429 x 310 x 368 mm	
Pan Turning Circle	Ø 660 mm	
Weight	29 kg	
ELECTRICAL		
Power Requirements	24Vac 50 / 60Hz or 24Vdc (±10%)	
Power Consumption	92VA Maximum	
TELEMETRY		
Interface	RS485 serial asynchronous data	
Protocols*2	Synectics™, Pelco®, and other industry standard protocols available	
Functions*1	Pan, Tilt, Zoom, Aux1, [Aux2] and Aux in	
Day/Night Camera	On / Off Selection of: Digital Zoom, BLC, Autofocus;	
Functions*1	Auto / Manual Selection of: Focus, Colour / Mono Operation, Frame Integration, White Balance	
Thermal Camera	3 step digital zoom (2x, 4x, 8x), Multiple Colour Palettes (including Inverted), Cross Hair Temperature Display,	
Functions*1	Auto / Manual Shuttering	
OSD	Password protected on-screen menu system for camera station configuration and diagnostics	
CAMERA / LENS		[OPTIONS]
	<b>C3000-2V36-T6&gt;&gt;[2C36] [W]*5</b>	<b>C3000-2V10-T6&gt;&gt;[2C10] [W]*5</b>
Video Output	1.0 Vpk-pk CVBS into 75Ω; Colour PAL 50Hz [NTSC 60Hz]	
Image Sensor	¼" EXview HAD CCD	⅓" Super HAD CCD II
Resolution	>550TVL	>530TVL
S/N Ratio	>50dB	
Zoom Range	36x zoom (up to 432x with digital zoom)	10x zoom (up to 120x with digital zoom)
Minimum Illumination	0.1 lux (with ⅓ sec integration) 0.01 lux mono (with ⅓ sec integration)	0.25 lux 0.0004 lux mono (with ⅓ sec integration)
Focal Length	3.4 to 122.4 mm	5.1 to 51 mm
Angle of View	57.8° to 1.7°	52° to 5.4°
Aperture	F1.6 to 4.5	F1.8 to 2.1
THERMAL IMAGER		[OPTIONS]
	<b>C3000-2V&lt;&lt;-T650 [2C&lt;&lt;] [W]*5</b>	<b>C3000-2V&lt;&lt;-T625 [2C&lt;&lt;] [W]*5</b>
Image Sensor	Uncooled VOx Microbolometer	
Spectral Response	8 – 14 μm	
Thermal Sensitivity	>50mK	
Refresh Rate	<9Hz [25Hz]	
Resolution	640 x 512	
Fixed Focal Length	50 mm	25 mm
Angle of View	12.4° x 9.9°	25° x 20°
Human Detection*3/4	~1100 m	~560 m

NOTE: \*1 Dependant on equipment fitted. \*2 Refer to Synectics for availability and compatibility with other control systems \*3 Based on Johnson Criteria. \*4 Actual range may vary depending on camera set-up, user experience, environmental conditions and type of monitor or display used. \*5 >> replace with thermal camera module and << replace with day / night camera module.

## Synectics

sales@synecticsglobal.com

[synecticsglobal.com](http://synecticsglobal.com)

Specifications subject to change. E & OE.

Copyright © Synectic Systems Group Limited, Synectic Systems, Inc., Synectic Systems (Asia) Pte. Limited 2018. All Rights Reserved.

MANUFACTURER OF  
  
 CAMERA STATIONS

Reference Numbers: 03GF0614\_2  
 C3000T2S6/0418/A4 Iss 6